

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924

Never - Seize

A02/083

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 133K ANTI-SEIZE LUBRICANT 80Z
 Item No: 80078
 Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
LITHIUM GREASE Mixture	30-40	5 mg/m ³ (oil mist)	5 mg/m ³ (oil mist)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	20-30	5 mg/m ³ mist	5 mg/m ³ mist
CALCIUM OXIDE 1305-78-8	15-25	2 mg/m ³	5 mg/m ³
GRAPHITE 7782-42-5	1-10	2 mg/m ³ respir.dust	5 mg/m ³ TWA respir.; 15mg/m ³ total
MINERAL OIL 64741-44-2	1-10	5 mg/m ³ TWA	10 mg/m ³ TWA
ALUMINIUM POWDER (PYROPHORIC) 7429-90-5	5-15	metal dust, as Al: 10 mg/m ³ TWA	total dust, as Al: 15 mg/m ³ TWA; respirable fraction, as Al: 5 mg/m ³ TWA
SILICA, QUARTZ 14808-60-7	0.1-1.0	0.1 mg/m ³ TWA respirable	0.1 mg/m ³ TWA respirable

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. May cause nose, throat and respiratory irritation. May cause gastrointestinal irritation. May cause central nervous system (CNS) depression.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness, difficulty breathing and vomiting. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Inhalation of dust at levels above recommended exposure limit may cause metallic or sweet taste, irritation of pharynx and possible ulceration with perforation of the nasal septum. Repeated skin contact may cause allergic skin reactions.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
SILICA, QUARTZ 14808-60-7	0.1-1.0	Known Carcinogen	Not known	Group 1; Vol. 68; 1997

Medical Conditions Recognized as Being Aggravated by Exposure: Persons with respiratory problems such as emphysema and asthma should avoid inhalation.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Greater than 200 degrees F. Method: Tag Closed Cup

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures:

Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products Formed by Fire or Thermal

Metal oxide fumes, Oxides of carbon. Incomplete combustion may emit component hydrocarbons.

Decomposition:

May ignite when sufficient heat is applied.

Unusual Fire/Explosion Hazards:

Lower Explosive Limit:

30% aluminum metal; 1% oil

Upper Explosive Limit:

7% oil

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

Handling:

Avoid prolonged skin contact. Keep away from eyes. Do not inhale vapors. Do not use near heat, sparks or open flame. Wash hands and face after handling this compound.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses or goggles.

Skin:

Neoprene or nitrile gloves recommended.

Ventilation:

Provide adequate local ventilation to maintain vapor concentration below TLV if misting of oil occurs.

Respiratory Protection:

Use an approved NIOSH organic vapor respirator below the TLV. If TLV is exceeded or overexposure is likely, use positive pressure or self contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Silver paste

Odor:

PETROLEUM

Boiling Point (°F):

Not determined

pH:

Does not apply

Solubility in Water:

Nil

Specific Gravity:

1.17

VOC Content(Wt.%):

Not determined

Vapor Pressure:

Less than 5 mm Hg

Vapor Density (Air=1):

Not Determined

Evaporation Rate:

Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

WILL NOT OCCUR

Incompatibilities:

Strong oxidizers, alkalies, mineral acids, selected amines.

Conditions to Avoid:

Do not expose to heat or store at temperatures above 120 F.

Hazardous Products Formed by Fire or Thermal

Metal oxide fumes, Oxides of carbon. Incomplete combustion may emit component hydrocarbons.

Decomposition:

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number:

D001

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name:

Unrestricted

Hazard Class:

NONE

Product name: 133K ANTI-SEIZE LUBRICANT 8OZ

Item 80078

UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Unrestricted
Class or Division: None
UN/NA Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 1

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA
06106

Revision Date: 09/16/2003
Revision Number: 2

Telephone Number: 1-87-Permatex (877) 376-2839